

Safetron SL630



Tootekirjeldus

- Preload technology
- Modern piston placement (equivalent to ASSA connect)
- Adapted for automatic door openers
- Fire rating: 120 min [E/EI 120]
- Split function, mechanical inside lever handle
- Simple function, electric activation both sides
- Easily adjusted between right or left
- Certified breaking strength: Grade 3
- **SL630:** fail secure latch bolt, fail safe handle activation
- **SL630 SECURE:** fail secure latch bolt, fail secure handle activation
- emergency exit according to EN 179:2008 with Emergency device 793 & 794
- Approved with type T emergency opener by Söderhamn innovation
- Handle movement indication
- Locked indication
- Door status indication (with magnet in strike plate)
- Knob/cylinder indication
- The product has been assessed by [Byggvarubedömningen](#)

- Back set 50 mm
- Latch bolt length: 14 mm

- Voltage: 12-24 VDC
- Power consumption:

Handle activation:

- 12 VDC: 70mA, 0mA at rest
- 24 VDC: 40mA, 0mA at rest

Duplication of functions:

- 12 VDC: 240mA, 0mA at rest
- 24 VDC: 240mA, 0mA at rest
- Micro switch: Max 30 VDC, 500mA
- Temperature range: -20°C - +40°C

TOOTENIMETUS	SOODUS	HIND
Đ¡Đ¾Đ»ĐµĐ½Đ¾Đ, Đ’Đ½Ñ ¹ Đ·Đ°Đ¼Đ¾Đ° Safetron SL630		806.08 €
Đ¡Đ¾Đ»ĐµĐ½Đ¾Đ, Đ’Đ½Ñ ¹ Đ·Đ°Đ¼Đ¾Đ° Safetron SL630 Secure		806.08 €
Đ¡Đ¾Đ»ĐµĐ½Đ¾Đ, Đ’Đ½Ñ ¹ Đ·Đ°Đ¼Đ¾Đ° Safetron SL630 + Đ¿Ñ€Đ¾Đ²Đ¾Đ’ + Đ°Đ°Đ±ĐµĐ»ĐµĐ¿Ñ€Đ¾Ñ Đ¾Đ Ñ<		900.35 €
Đ¡Đ¾Đ»ĐµĐ½Đ¾Đ, Đ’Đ½Ñ ¹ Đ·Đ°Đ¼Đ¾Đ° Safetron SL630 Secure + Đ¿Ñ€Đ¾Đ²Đ¾Đ’ + Đ°Đ°Đ±ĐµĐ»ĐµĐ¿Ñ€Đ¾Ñ Đ¾Đ Ñ<		900.35 €



