

ASSA ABLOY DC700GCM



Tootekirjeldus

- Door closer with Cam-Motion® technology, extended mounting plate and integrated Close-Motion® element for safe and noiseless closing
- The door can be pulled closed safely and quietly from an angle of $\approx 10^\circ$
- Suitable for retrofitting on fire doors and smoke control doors and fastening using drilling template in accordance with DIN EN 1154, supplementary sheet 1:2003-11
- Suitable for fire and smoke protection doors with tamper protection
- Tested as a whole element in accordance with EN 1154, size 3-6
- For single action doors up to 1400 mm wide
- Meets the requirements of DIN SPEC1104 / CEN TR15894

Note

- Suitable for fire and smoke protection doors with tamper protection

Characteristics DC700G-CM

- Integrated Close-Motion® element in extended closer housing
- Close-Motion® element with horizontal and vertical adjustment
- Optional tamper protection, installation without dismantling function elements
- Standard installation on hinge side
- Can be used for left and right-handed doors
- Axis continuously height adjustable up to 14 mm

- Closing speed and latching speed continuously adjustable from front
- Variable adjustable closing force
- Opening angle ca. 170°
- Thermodynamic valves for consistent speed
- Standard colours: Silver EV1, stainless steel design

Compatible products:

- Sliding arm: [G150](#)

TOOTENIMETUS	SOODUS	HIND
ð´ðµÑ•Ñ^Ñfð¹⁄₄ð¹⁄₂Ñ<ð¹ ð´ð³⁄₄ð²ð³⁄₄ð´Ñ‡ð³ð° ASSA ABLOY DC700, ð¹⁄₂ð°ð´ðµð¶¹⁄₂ð³⁄₄ ð·ð°ð°Ñ€Ñ<ð²ð°ðµÑ, ð´ð²ðµÑ€Ñœ (EN 3-6)		883.11 €



