

Safetron 6600



Tootekirjeldus

- Certified according to. SSF 3522: lock class 2B, 3, 4 and 5.
- Certified according to. SS-EN 14846: Security Grade 7
- Certified according to. SS-EN 179 (emergency exit)
- Backset 50 mm
- Hook rule
- latch bolt
- Fire rating E/EI 120
- Built-in sensors: rule in, rule out, door status (magnetic contact).
- OSDP® via RS-485
- 128-bit AES encryption
- Disengagement: 0.1 seconds
- Openable with key/knob (90 degree turn)
- emergency exit together with emergency exit accessories 796
- Re-entry selectable in controller
- Plug and play installation
- Up to 100m cable between motor lock and controller
- Event log
- Service module in control unit
- Series connection, up to two motor locks to one controller

- 10-48VDC
- Power consumption:

Motor lock 6600

12VDC: Rest: 20mA / Max: 200mA

24VDC: Rest 10mA / Max: 100mA

Motor lock 6600 + Controller CU2

12VDC: Rest: 120mA / Max: 300mA

24VDC: Rest 60mA / Max: 150mA

- Working temperature -30°C to +70°C
- Suitable for Scandinavian oval and round cylinders

TOOTENIMETUS	SOODUS	HIND
Motor lock Safetron 6600		1336.12 €
Motor lock Safetron 6600 + striker plate + cable + lead cover		1470.73 €
Motor lock Safetron 6600 + striker plate + cable + lead cover + control unit		1999.21 €



